

REQUEST FOR QUOTATION

RFQ NUMBER BRC 2020-RFQ-001

RFQ TITLE Supply and Delivery of One (1) Diesel 8T Payload Truck with

8,000L Water Tank

CLOSE DATE 2:00 p.m. Australian Central Standard Time

WEDNESDAY 19TH August 2020

(LATE TENDERS MAY NOT BE ACCEPTED)

HOW TO RESPOND TO THIS REQUEST FOR QUOTATION

Complete this Tender Response Schedule provided. This will become your Tender which may be lodged in the following way:

By electronic lodgement facility via Vendor Panel at localbuy.com.au or TenderLink.com or

By email to maricar.rhodes@barkly.nt.gov.au

NOTE: No other form of delivery is acceptable.

Contents

CON	IDITIONS OF QUOTING	4
1.	Interpretation of Terms	4
2.	Preparing a Quotation	4
2.1	General Requirements	4
2.2	Respondents to Inform Themselves	4
2.3	Quotation Costs	4
2.4	Compliance with NT Procurement Code	5
2.5	Enquiries	5
2.6	Probity Advisor	5
2.7	Addendum	5
2.8	Best Offer	5
3.	Closing Date and Time	5
4.	Quotation Validity	6
5.	Alternative Quotations	6
6.	Part Offer and Part Acceptance	6
7.	Pricing	6
7.1	General Requirements	6
7.2	Treatment of Low or Aberrant Prices	6
7.3	Competitive Neutrality	6
8.	Conflict of Interest	7
9.	Panel Period Contract	7
10.	Local Content	7
11.	Admissibility	7
12.	Ownership of Documents	7
13.	Changes to the Conditions	8
13.1	Conditions of Quoting	8
13.2	Conditions of Contract	8
14.	Assessment Criteria	8
15.	Conduct of the Assessment	8
15.1	General	8
15.2	Clarification and Additional Information	8
15.3	Security, probity and financial checks	8
16.	Negotiations	9
17.	Notice of Acceptance	9
18.	Unsuccessful Quotations	9
REQ	UEST FOR QUOTATION	10

R	FQ Number: (To be filled out)	10
R	FQ Title: SUPPLY AND DELIVERY OF ONE (1) Diesel 8T Payload Truck with 8,000L Water Tank	10
Spe	cific Requirements of the Contract	10
TEC	HNICAL SPECIFICATIONS	11
RES	PONSE SCHEDULE A	14
1.	Information Required	16
2.	Price Schedule	. 17

CONDITIONS OF QUOTING

1. Interpretation of Terms

Unless the contrary intention is indicated these Conditions of Quoting are to be interpreted in the same manner and words have the same meaning as in the Contract.

If a date stipulated for doing an act in relation to the RFQ is not a business day (being any day which is not a Saturday, Sunday or public holiday in the Northern Territory, as specified in Schedule 2 of the Public Holidays Act (NT), the act must be done on the next business day.

In these Conditions of Quoting the following definitions apply:

"Addendum" means any document expressly stated to be an Addendum which is issued by the Principal varying, updating or clarifying the RFQ prior to the stated time and date for closing of the RFQ.

"Annexure" means the document titled "Annexure to the Conditions of Quotation and Contract" and contained in in this RFQ.

"Contract" means the document titled "Conditions of Contract" and referenced or contained in this RFQ.

"Principal" means the "Barkly Regional Council."

"RFQ" means the request for quotation inviting offers and includes all conditions, annexures, schedules, attachments and addenda.

'Supplies" means the works, goods and/or services required by the Principal and described in this RFQ.

"Quotation" means all documents lodged by the Respondent in response to the RFQ.

"Respondent" means the person lodging a Quotation.

2. Preparing a Quotation

2.1 General Requirements

Each Quotation is required to contain one copy of the documents listed in the section of the Annexure titled "Documents to be Lodged." Failure to provide all documents may result in the Quotation being declared inadmissible for assessment.

Quotations should contain:

- a) If the Respondent is one or more individuals, the full names of each party;
- b) If the Respondent is one or more company or organisation, each company, business or trading name and each unique business identifier required by law (e.g. ACN/ARBN/ABN);
- c) The address for service of any notices necessary or required to be or which may be served on or given to the Respondent in connection with its Quotation and any subsequent contract arising out of acceptance of the Quotation.

Each Quotation (excluding attachments or supplementary information provided by the Respondent) must be in English. A Quotation that does not comply with this requirement will be declared inadmissible for assessment.

2.2 Respondents to Inform Themselves

Respondents must, at their own expense, inform themselves of all circumstances and conditions relating to submitting a Quotation and providing the Supplies. This includes compliance will all legislation, an inspection of the relevant site(s) and satisfying themselves as to the correctness and sufficiency of the RFQ documentation.

2.3 Quotation Costs

The Respondent is responsible for all costs associated with preparing a Quotation.

Barkly Regional Council ("the Principal") will not be liable for an expense or loss, which may be incurred by any Respondent in the preparation or submission of its Quotation.

2.4 Compliance with NT Procurement Code

In preparing its Quotation, submitting its Quotation and throughout the quoting period, the Respondent must comply with the **Northern Territory Procurement Code** ("Code").

If the Principal is of the reasonable opinion that the Respondent has not complied with the Code, the Principal will declare the Quotation inadmissible for assessment.

2.5 Enquiries

Should the Respondent

- a) Have any doubts as to the meaning of any part of the RFQ; or
- b) Find any discrepancy, error or omission in the RFQ;

The Respondent should seek clarification from the Barkly Regional Council, as identified in the Annexure, as early as possible but in any event before the stated time and date for closing of the RFQ.

Barkly Regional Council may decline to provide a clarification or further information requested by the Respondent.

Any clarification provided by Barkly Regional Council may be provided to all prospective Respondents.

Enquiries are directed to <u>Richard James</u> (Municipal Services Manager) at (08) 8962 0083 or <u>Maricar Rhodes</u> (Procurement) at (08) 8962 0028.

2.6 Probity Advisor

Barkly Regional Council may appoint an independent probity advisor to advice on probity issues arising during the course of the RFQ process. The details of the probity advisor, if any, will be contained in the Annexure. Any issues about the integrity of the RFQ process should be addressed to the probity advisor.

2.7 Addendum

Barkly Regional Council may vary, update or clarify the RFQ at any time before the stated time and date for closing of the RFQ through the issue of an Addendum.

No explanation or amendment to the RFQ will be binding unless in the form of an Addendum. Any Addendum issued under this clause will become part pf this RFQ.

It is the sole responsibility of the Respondents to ensure that their contact details held by Vendor Panel at localbuy.com.au or Tenderlink.com are correct and up-to-date in order for them to receive the Addendum.

2.8 Best Offer

Notwithstanding anything which may be done pursuant to the assessment process, Barkly Regional Council intends to select the successful Respondent primarily on the basis of the Quotations lodged but will also take into consideration any other information publicly available or known to the Principal. Accordingly, Respondents should provide their best offer in the Quotation.

3. Closing Date and Time

Tender closes at 2:00 pm Australian Central Standard Time on Wednesday, 19th of August 2020.

Quotations are to be received, in full, by the time and date for closing of the RFQ.

Failure to lodge a Quotation, or part thereof, before the time and date for closing of the RFQ may result in the Quotation being declared inadmissible for assessment.

4. Quotation Validity

Quotation Responses must remain valid and open for acceptance by Barkly Regional Council for the period stated in the Annexure.

Where the Principal seeks an extension to the validity of the offer, a request will be forward to Respondents in writing and, within the time period stated in the request, a Respondent may by notice in writing:

- a) Withdraw their Quotation Response; or
- b) Agree to extend the validity of their offer for the requested period.

A failure to respond, or a failure to withdraw or agree in writing, within the time period stated in the request may result in the Quotation Response being deemed withdrawn by the Respondent and not considered further.

5. Alternative Quotations

Respondents are required to submit a Quotation which conforms to the requirements of the RFQ. **No alternative quotations are allowed.**

6. Part Offer and Part Acceptance

Unless otherwise state in the Annexure, Respondents are required to offer for the whole of the Supplies.

If part offers are permitted by the Annexure, the Principal reserves the right to accept a portion or the whole of any Quotation at the price or prices submitted unless the Respondent specifically states to the contrary in its offer.

7. Pricing

7.1 General Requirements

Unless otherwise specified, prices must:

- a) Be stated in Australian Dollars;
- b) Be inclusive of:
 - i. GST (where applicable);
 - ii. All costs required to provide the Supplies, including labour, materials, transport, freight, overheads, profits and charges; and
 - iii. All other fees, duties and taxes required to provide the Supplies.

7.2 Treatment of Low or Aberrant Prices

Where a price (or a key element of a Quotation price) is considered well below or above the median price or the Principal's estimated value, the Respondent may be requested to confirm the quoted price or respond to questions regarding particular aspects of the Quotation. The Respondent may also be requested to provide written confirmation that the requirement and contractual obligations relevant to the Supplies are fully understood.

The Principal may, at its discretion, either:

- a) Proceed with the evaluation of the Quotation; or
- b) Where there is evidence that acceptance of the Quotation may result in an unacceptable contract outcome or pose a substantial risk to the provision of the Supplies or the sustainability of the Respondent, set the Quotation aside from further assessment.

7.3 Competitive Neutrality

Government-owned businesses, Local, Territory, State and Federal Government agencies and authorities responding to this RFQ must submit two prices against each item in the pricing schedule. One price is to be quoted price offered and the other being the adjusted competitively neutral price. The competitively neutral price is to be prepared in accordance with the "Northern Territory Government's Competitive Tendering Guidelines."

8. Conflict of Interest

For the purpose of this clause a "Conflict" means any matter, circumstance, interest, or activity affecting the Respondent (including the officers, employees, agents and subcontractors of the Respondent) which may or may appear to impair the ability of the Respondent to perform any contract resulting from this RFQ diligently and independently.

Respondents must declare any Conflict in their Quotation.

Respondents must not place themselves in a position that may, or does give rise to a Conflict during the RFQ process.

If at any time during the RFQ process, a Respondent is aware that an actual, potential or perceived Conflict exists or may arise, that Respondent must immediately notify Barkly Regional Council.

If a Conflict exists or arises during the RFQ, Barkly Regional Council may:

- a) Declare the Quotation inadmissible for assessment;
- b) Enter into discussions to seek to resolve the Conflict; or
- c) Take any other action it considers appropriate.

9. Panel Period Contract

Where specified in the Annexure, the Principal may establish a panel of suppliers for the provision of the Supplies. The resulting contracts will be for either:

- a) Specific requirements at fixed unit rates; or
- b) For a general scope of requirements without any rates, and for which firm offers will be periodically sought from the suppliers.

10. Local Content

Barkly Regional Council is committed to supporting businesses that use local contractors and supplier and hire and train Territorians. Assessment will take into consideration businesses that demonstrate a commitment to supporting and employing Territorians including indigenous Territorians, accredited training for its employees and sourcing goods and services from local businesses.

11. Admissibility

Unless otherwise specified, if a Respondent fails to comply with a requirement as set out in these Conditions of Quoting, their Quotation may be declared inadmissible for assessment.

In determining whether a Quotation is admissible for assessment, Barkly Regional Council will consider:

- a) Whether admitting the Quotation will compromise the integrity of the quotation process;
- b) Whether the Respondent has or is likely to gain an unfair advantage;
- c) Reasons for the Respondent's failure to comply with a requirement;
- d) Whether the Quotation is capable of assessment;
- e) Whether the Quotation was mishandled by Barkly Regional Council or a third party; and
- f) Evidence of unfair practices.

Barkly Regional Council may, in its absolute discretion, declare a Quotation inadmissible for assessment where, in the reasonable opinion of Barkly Regional Council (being based on fact or a reasonable belief), the Respondent has engaged in "improper conduct" as that term is defined in the *Independent Commissioner against Corruption Act* 2017 (NT).

12. Ownership of Documents

All Quotations become the property of Barkly Regional Council upon submission and will not be returned to Respondents.

By lodging a Quotation, a Respondent licenses Barkly Regional Council to reproduce the whole or any portion of the Quotation for the purposes of the conduct of the RFQ, including assessment, clarifications, resultant contract negotiation, contract management, and anything else in relation to these purposes.

13. Changes to the Conditions

13.1 Conditions of Quoting

Respondents are not permitted to request changes or propose alternatives to these Conditions of Quoting. Any Respondent who proposes a change will be requested to withdraw the change in order to comply with the Conditions of Quoting. If the changes are not withdrawn, the Quotation will be declared inadmissible for assessment.

13.2 Conditions of Contract

If permitted in the Annexure, Respondents may request changes to the Conditions of Contract, or propose alternative conditions of contract.

Where Respondents request changes to the Conditions of Contract or propose alternative conditions of contract, they must clearly specify in the appropriate section of the Response Schedules the changes to the Conditions of Contract that are being requested or the alternative conditions of contract that are being proposed.

Where Respondents request changes to the Conditions of Contract or propose alternative conditions of contract, they do so at their own risk, as the changes will be deemed to have formed part of their offer and their Quotation will be assessed on that basis. If the requested changes or the alternative conditions of contract are not acceptable to the Principal, the Quotation may not be successful.

Nothing in this clause affects Barkly Regional Council's right to negotiate with one or more Respondents as provided for in this RFQ.

14. Assessment Criteria

Selection of the successful Respondent will be based on a "Best Value for Territory" assessment of the Quotation against the assessment criteria specified in the Annexure.

15. Conduct of the Assessment

15.1 General

Barkly Regional Council may disclose information acquired or developed during the assessment process (including a copy of the Quotation) to Ministers and other Government representatives, consultants, advisors, other Agencies and statutory authorities for the purpose of the assessment, clarification, negotiation and reporting of this RFQ and in order to comply with the law and enable effective management, review or auditing of Barkly Regional Council's activities.

15.2 Clarification and Additional Information

The Respondent may be called to clarify information contained in their Quotation or to supply information in addition to the Quotation to demonstrate to the satisfaction of Barkly Regional Council that the Respondent has the ability to provide the Supplies.

The Respondent must within the time specified comply with any such requests. Failure to submit any or all of the information required, in the time stipulated, may result in the Quotation being declared inadmissible for further assessment.

15.3 Security, probity and financial checks

Barkly Regional Council reserves the right during any part of the assessment of Quotations to perform such security, probity and financial investigations and checks as Barkly Regional Council may determine are necessary in relation to Respondents, their employees, officers, partners, associates, subcontractors or related entities and their employees, officers and subcontractors. These checks may include (without limitation):

- a) Security;
- b) Financial viability and technical capacity;
- c) Corporate history;
- d) Significant litigation (past, present or pending); and

e) Any other matters Barkly Regional Council considers relevant.

Respondents must, at their cost, promptly provide Barkly Regional Council with such information or documentation that Barkly Regional Council requires in order to undertake such investigations or checks.

Barkly Regional Council may declare a Quotation inadmissible for further assessment if the Respondent does not promptly provide all reasonable assistance to the Principal in this regard or based on the outcomes of the investigations or checks.

16. Negotiations

- a) Barkly Regional Council may engage in detailed discussions and negotiations with one or more Respondents.
- b) The selection of Respondents under this clause does not bind Barkly Regional Council to a contractual relationship and is not an indication that the Respondent will be successful.
- c) The result of any successful negotiations will be incorporated into the Contract.

17. Notice of Acceptance

Barkly Regional Council will not be bound to accept the lowest or any Quotation.

The successful Respondent will be notified in writing on the completion of the RFQ process ("Notice of Acceptance").

Unless otherwise specified, the "Notice of Acceptance" forms a binding agreement between Barkly Regional Council and the successful Respondent on the terms set out in the Contract. The "Notice of Acceptance" will, at Barkly Regional Council's discretion, be issued by pre-paid post, facsimile or email to the address stated in the Quotation.

A Respondent should not act on any representations or statements made by Barkly Regional Council, its employees or agents prior to the issue of the "Notice of Acceptance."

Barkly Regional Council may publish details of the successful Quotation, including the name and address of the Respondent, value of the contract awarded and a description of the Supplies.

Respondents may request a debriefing as to why their Quotation was successful. This is for the purpose of assisting Respondents to improve their competitiveness for future Quotations.

18. Unsuccessful Quotations

Unsuccessful Respondents will be informed in writing of the outcome of their Quotation at the conclusion of the RFQ process.

Respondents may request a debriefing as to why their Quotation was unsuccessful. This is for the purpose of assisting Respondents to improve their competitiveness for future Quotations.

Information will be confined to discussion of the Respondent's Quotation and under no circumstances will information relating to another Quotation be disclosed.

RFQ Number: BRC 2020-RFQ-001

RFQ Title: SUPPLY AND DELIVERY OF ONE (1) Diesel 8T Payload Truck with 8,000L Water Tank

The Barkly Regional Council invites suitably qualified suppliers to submit quotations for the **SUPPLY AND DELIVERY** of One (1) Diesel 8T Payload Truck with 8,000L Water Tank (referred hereon as "Water Truck"). The Delivery Location is at the Barkly Regional Council Depot, 1 Maloney Street, Tennant Creek, Northern Territory 0860.

The Respondent is to note that any liability before delivery such as in-transit insurance shall be the responsibility of the supplier.

Quotations must be in accordance with the Technical Specifications and Criteria.

Tender closes at 2:00 pm Australian Central Standard Time on Wednesday, the 19th of August 2020.

Quotations are to be received, in full, by the time and date for closing of the RFQ.

Failure to lodge a Quotation, or part thereof, before the time and date for closing of the RFQ may result in the Quotation being declared inadmissible for assessment.

Specific Requirements of the Contract

The "Water Truck" shall be of current manufacture as being sold, serviced and used in the Northern Territory. The Water Truck shall comply with all relevant Acts, Regulations, associated ADRs and Technical Specifications. Where any part of this specification contradicts the before-mentioned legislative frameworks, the legislative frameworks will take precedence and the Respondent shall also notify Barkly Regional Council of any discrepancies and/or contradictions so identified.

The Vehicle shall be delivered "registered as a road vehicle."

Schedule "A" of the Response Form must be completed and submitted with the RFQ. Respondents are to include any additional details and specifications relevant to their submission which will be deemed to form part of the RFQ. Non-completion of all or part of Schedule "A" of the Response Form may render inadmissibility for further assessment.

Suppliers who provide goods and/or services to Barkly Regional Council must do so in compliance with the Work Health and Safety (National Uniform Legislation Act 2011).

Quoted Prices are to be on a Lump Sum Basis inclusive of Goods and Services Tax (GST). Pricing to include NT Registration and Delivery to the Barkly Regional Council Depot at 1 Maloney Street, Tennant Creek, Northern Territory 0860. Additional charges not stated in the RFQ Response Schedule will not be allowed as a Charge for any transaction under any resultant contract.

TECHNICAL SPECIFICATIONS

	Truck Specifications
General	Rigid Body Truck (Chassis Only)
	Colour White
	Current Year of Manufacture at the time of Tender
	Registered to Council's common date of 1 February 2021. Council uses
	QBE for its insurance needs. Registration costs are not to be included in
	the Tender and will be paid at the time of delivery
Engine	Diesel
	Approximately 265 KW
	Council uses Castrol Vecton Long Drain 15W40 engine oil. Suppliers are
	to advise Barkly Regional Council the suitability of this oil for use in the
	truck
	Hour Meter
Load	Payload approximately 8.0T
	Full length mass distribution diagram with tank and water is to be
	provided
Transmission	Automatic
	4 x 2
	Rear axle differential inter-axle cross locks are to be fitted
	Transmission cooler to be fitted
Hydraulics	For the operation of the water tank, a "hot shift" PTO and hydraulic
	pump shall be fitted
	All hydraulic lines and fittings to be installed. Hydraulic couplings to be TEMA 10000
	Suction and return filters are to be installed and to be of adequate size
	Suction and return inters are to be instance and to be or adequate size
Axle	Front (Steer) axle camber angle shall be corrected to suit Northern
	Territory road conditions. Certificate to be provided on delivery.
Brakes	All service brakes
	Air brake couplings are to be fitted for Trailer Brakes
	Engine Brake
Cabin	Single Cab
	Fitted with three (3) seats. One (1) driver, two (2) passengers
	Driver's seat-air suspension (ISRI or equivalent) and adjustable, fore, aft,
	up and down including adjustable suspension settings for varying driver
	mass
	Canvass seat covers
	Floor and dash mats
	CD with AM/FM Radio with USB and Bluetooth functionality
	VHF, Digital radio Motorola DM4601eA5 to be fitted. Serial Nos. of all
	hardware to be listed
	GME or Unidem RM770 equivalent 40 Channel UHF
	Factory air conditioning
	12v cigarette lighter socket
	Seatbelts with pre-tensioner

	Dual "west coast" type rear view electric mirrors. Spot mirrors are also			
	required on both sides			
	Cab tilt electric hydraulic with a manual jack in the event of power failure			
	of the main source			
De du	District (Chancis Only)			
Body	Rigid (Chassis Only)			
	Heavy duty anchor points for vehicle recovery front and rear			
	Rear Lights Stop, Tail, Reverse and Indicators to be LED and to be fitted with protection			
	25-litre underbody water tank with 12mm tap to be fitted			
	A tyre inflation kit shall be fitted with sufficient hose supplied Tow coupling heavy duty pintle and 70mm ball combination			
	Full length mud guards and mud flaps for all wheels			
	Fuel Tank with a lockable fuel cap and an anti-syphoning device installed			
	A large seven-pin 12 and 24V trailer plugs to be fitted A waterproof lockable heavy duty toolbox of approximately 150 litres			
	capacity –			
	(750mm x 500mm x 400mm) fitted underbody if room allows or on front			
	passenger side of the tank sub-frame. If underbody minimum 500mm			
	clearance to ground			
	dictional to give and			
Spare Wheel	One (1) Spare wheel to be supplied and mounted in a suitable location			
1				
Extras	Two (2) work lights to be installed-one (1) on each side in appropriate			
	locations			
	Dual LED flashing lights to be fitted to the roof of the vehicle			
	Audible reversing indicator minimum noise level 90 dB			
	Reversing camera mounted in a protected position and above the spray			
	units			
	Automatic greasing system			
	Automatic greasing system An external and easy access lockout isolator switch			
	An external and easy access lockout isolator switch			
	An external and easy access lockout isolator switch All external wiring to be in conduit			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred.			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied			
	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender.			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate the need for access to top of tank to close the lid			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate the need for access to top of tank to close the lid Access rail/steps to top of tank compliant with relevant OH&S			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate the need for access to top of tank to close the lid Access rail/steps to top of tank compliant with relevant OH&S regulations			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate the need for access to top of tank to close the lid Access rail/steps to top of tank compliant with relevant OH&S regulations Contains two (2) sight glasses with a Hi-Vis float at the rear and front			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate the need for access to top of tank to close the lid Access rail/steps to top of tank compliant with relevant OH&S regulations			
General	An external and easy access lockout isolator switch All external wiring to be in conduit Tare, GVM and GCM stickers to be fitted Tyre pressure requirements to be posted for easy vision of operators Access to manufacture diagnostic software an any maintenance/repair software shall be provided All relevant workshop, parts and operator manuals in CD or hard copy to be supplied with Truck. CD is preferred. A full Risk Assessment Report is to be supplied Tank Specifications 8.000-Litre Poly Tank Colour White To be internally baffled The tank is to be mounted on a sub-frame to the truck. Sub-frame is to be compliant with the relevant standards. This standard is to be specified by the supplier in the tender. Tank to solid pin mounted to the frame Tank manhole to be of tapered design, non-splash and no lid to eliminate the need for access to top of tank to close the lid Access rail/steps to top of tank compliant with relevant OH&S regulations Contains two (2) sight glasses with a Hi-Vis float at the rear and front			

mounted at each side of vehicle One (1) 3" fully-adjustable butterfly/magnum spray head located at centre of tank mounted on cam lock fitting. Capped/sealed pipework to extend to either side of the rear of tank to accommodate future side spray valve. Install if required Minimum two (2) gravity sprays at rear left and right with cam lock fittings. Discharge to be gravity or pressurised Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied				
One (1) 3" fully-adjustable butterfly/magnum spray head located at centre of tank mounted on cam lock fitting. Capped/sealed pipework to extend to either side of the rear of tank to accommodate future side spray valve. Install if required Minimum two (2) gravity sprays at rear left and right with cam lock fittings. Discharge to be gravity or pressurised Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied	Sprays	2 x 2 inch front mounted individually activated gutter flusher fan sprays		
centre of tank mounted on cam lock fitting. Capped/sealed pipework to extend to either side of the rear of tank to accommodate future side spray valve. Install if required Minimum two (2) gravity sprays at rear left and right with cam lock fittings. Discharge to be gravity or pressurised Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied				
extend to either side of the rear of tank to accommodate future side spray valve. Install if required Minimum two (2) gravity sprays at rear left and right with cam lock fittings. Discharge to be gravity or pressurised Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		One (1) 3" fully-adjustable butterfly/magnum spray head located at		
spray valve. Install if required Minimum two (2) gravity sprays at rear left and right with cam lock fittings. Discharge to be gravity or pressurised Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		centre of tank mounted on cam lock fitting. Capped/sealed pipework to		
Minimum two (2) gravity sprays at rear left and right with cam lock fittings. Discharge to be gravity or pressurised Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied				
Hoses Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		spray valve. Install if required		
Hoses Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		Minimum two (2) gravity sprays at rear left and right with cam lock		
firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		fittings. Discharge to be gravity or pressurised		
firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised 15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied				
15M of suction hose with storage rack/storage cavity. The storage rack/cavity is to under to avoid the need to climb up the tank Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied	Hoses	Heavy duty 20 M, 1" pressure hose and retractable reel. Adjustable		
Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		firefighting nozzle to be fitted. Discharge to be gravity fed or pressurised		
Pump and Valve Control System A separate filler pipe discharging to the top of the tank and that it will bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		15M of suction hose with storage rack/storage cavity. The storage		
bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		rack/cavity is to under to avoid the need to climb up the tank		
bypass the tank's integral hydraulic pump for filling from an external pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied				
pressurised water supply of from a stand pipe Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied	Pump and Valve Control System	A separate filler pipe discharging to the top of the tank and that it will		
Oil cooling will be via a cooler mounted on the tank sub-frame. Please note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		, , , , , , , , , , , , , , , , , , , ,		
note that the truck will operate in very hot (37 to 40 degrees) and dusty conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		pressurised water supply of from a stand pipe		
Conditions Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		Oil cooling will be via a cooler mounted on the tank sub-frame. Please		
Valve Controls: Electric Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		note that the truck will operate in very hot (37 to 40 degrees) and dusty		
Return valves are to fitted to return to tank when sprayers are turned off Quantity two (2) RF handheld remote controls for pump and valves Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		conditions		
Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		Valve Controls: Electric		
Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		Return valves are to fitted to return to tank when sprayers are turned		
Others Rear lights LED and recessed for protection. AS compliant LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		off		
LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		Quantity two (2) RF handheld remote controls for pump and valves		
LED flashing light fitted at the top of the tank. AS compliant. Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied				
Side LED clearance lights recessed 4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied	Others	Rear lights LED and recessed for protection. AS compliant		
4.5kg fire extinguisher with quick release mounting bracket mounted on front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		LED flashing light fitted at the top of the tank. AS compliant.		
front of body in an accessible position Workshop, spare parts and operator manuals to be supplied		Side LED clearance lights recessed		
Workshop, spare parts and operator manuals to be supplied				
		front of body in an accessible position		
		Workshop, spare parts and operator manuals to be supplied		
Do not overtake turning verifice signage to be nitted at the real		Do not overtake turning vehicle signage to be fitted at the rear		

The successful Tenderer shall provide full <u>operator induction training</u> for operators and maintenance training on programmed maintenance procedures and fault finding for maintenance personnel on site at Barkly Regional Council's Tennant Creek Depot at 1 Maloney Street at the time of delivery of the unit.

The successful Tenderer will also be required to provide a comprehensive list with part numbers of all consumable items.

This list will include oil, fuel, air, hydraulic and cab fitters as well as all other fast-moving items required for servicing and maintaining the vehicle supplied.

RESPONSE SCHEDULE A

TENDERER'S DETAILS Legal Entity Name Trading as ABN ACN **CAL Registration** (Required only when specified in the annexure) Number Address of Place of Business **Postal Address** Telephone Facsimile **Email Address** Web Site **CONTACT PERSON DETAILS** Name Position Telephone Facsimile **Email Address**

On behalf of the Tenderer, I/We the undersigned hereby:

Conditions of Contract

1. Agree to be bound by the Conditions of Contract as referred to in Section 2 of the Request for Quotation

Business Status

- 2. Certify to the best of my/our knowledge:
 - a) If the Tenderer is an individual, that he or she:
 - (i) is not a bankrupt; or
 - (ii) has not assigned his or her estate for the benefit of creditors.
 - b) If the Tenderer is a partnership, no step has been taken to dissolve that partnership.
 - c) If the Tenderer is a company:
 - (i) that no application or order has been made for the winding up of the company (whether voluntary or otherwise);
 - (ii) that no resolution has been passed for the winding up of the company; or
 - (iii) that the company is not under:
 - (A) an arrangement and/or reconstruction (i.e. restructuring a public company);
 - (B) an appointed liquidator, provisional liquidator or administrator;
 - (C) an appointed receiver or manager (or both);
 - (D) official management; or
 - (E) any composition or arrangement or assignment with, or for the benefit of, its creditors or a class of them.

Offer

- 3. Having examined and acquired an actual knowledge of the Request for Tender offer to provide the Services at the amount(s) quoted and in accordance this Request for Tender and completed schedules attached.
- 4. Agree the offer shall remain valid for acceptance for a period of 60 days from the closing date.

Please acknowledge acceptance of the above by placing an "X" in this box				
Signature		Date		
Name		Position		

(Print name and position in business)

(*Add additional signature block as necessary)

1. Information Required

Specification Detail	
Make/Model	
Engine Power (KW)	
Warranty	
Engine and Transmission Oil Types and Grades	
GVM	
GCM	
Payload	
Full length mass distribution diagram with full tank of water	
Driver's Seat Type	
Make/Model of Auto Greasing System	
Time and Resources allocated for Induction Training	
Fuel Tank Capacity	
Cab Tilt	
Spotlight Make and Model	
Water Tank Capacity	
Baffles (Provide details)	

The successful Tenderer shall provide full <u>operator induction training</u> for operators and maintenance training on programmed maintenance procedures and fault finding for maintenance personnel on site at Barkly Regional Council's Tennant Creek Depot at 1 Maloney Street at the time of delivery of the unit.

The successful Tenderer will also be required to provide a comprehensive list with part numbers of all consumable items.

This list will include oil, fuel, air, hydraulic and cab fitters as well as all other fast-moving items required for servicing and maintaining the vehicle supplied.

2. Price Schedule

Please provide a price for the "Water Truck" as it would be ex-factory (bare), and a price for all additional items and accessories as specified including a delivery cost to Barkly Regional Council Depot located at 1 Maloney Street, Tennant Creek, Northern Territory 0860.

Do not include Registration and CTP costs in the Quoted Prices.

Description	Price for a Bare Truck (GST inclusive)	Cost of accessories As Specified on this Tender (GST inclusive)	Total cost of Water Truck and Accessories (including GST)
			(1 1 1 0 1 1

Any specifications	not met:				
1.					
2.					
3.					
4.					
	_				ording to the Technica hat the prices above are
the prices Barkly F	Regional Council	will evaluate or	1.		
Delivery Time from	n Placement of (Order:			
benvery rune nor	in ideement or c				
Signature				Date	
Name				Position	
		(Print name and p	osition in business)		

(Print name and position in business)